
UTILITY PULLER 6K™

MINIMAL SET-UP WITH THE TRUCK MOUNTED BI-DIRECTIONAL BOOM





With the hardworking Utility Puller 6K, you can transfer heavy pulling loads to the ground within inches of the conduit you're pulling through. For overhead pulls, line guide rollers keep the rope centered on the capstan.





Mounts in 2" receiver stock



Pull overhead lines



Boom articulates for underground applications

FASTER SAFER WORKSPACE





UTILITY PULLER 6K™

MINIMAL SET-UP WITH THE TRUCK MOUNTED BI-DIRECTIONAL BOOM

2-SPEED MOTOR

with reverse





keep rope centered

DUAL CAPSTANS

3,000 lb large capstan capable of pulling 20' & 70' per minute

6,000 lb small capstan capable of pulling 8' & 28' per minute **TELESCOPING TUBING**

to match any grade

MOUNTS TO 2"
RECIEVER STOCK

ADJUSTABLE FRONT ROLLER

allows you to position pulling rope at the center of the conduit

*Sold as Shown

BI-DIRECTIONAL BOOM

allows for precise puller set-up

STABLE T-FOOTPRINT

Model Description Specifications

UP6K

Utility Puller 6K™ 11A 120V AV Motor 20"H x 20"W x 75" L (Collapsed) 20"H x 20"W x 114" Extended 130 lb. (6,000 lb. Load Capacity)

UPC# 650270083939





*For transportation purposes. Do NOT exceed 25 mph while loaded in receiver hitch.

Patent Pending