



1325 Carden Farm Dr. Clinton, TN 37716 (865)670-3713

Crimp ID, OD, Specs for Alum & Copper

Crimp Part #	Conductor Size	Lanyard Length	Lanyard Wire Rope Diameter	Crimp IDin	Crimp OD in	Minimum Conductor Size (dia in)	Maximum Conductor Size (dia in)
CR120	8	11"	1/16"	0.18	0.34	0.134	0.146
CR121	8	15"	1/16"	0.18	0.34		
CR122	8	19"	1/16"	0.18	0.34		
CR123	8	23"	1/16"	0.18	0.34		
CR124	6	11"	1/16"	0.218	0.338	0.184	0.169
CR125	6	15"	1/16"	0.218	0.338		
CR126	6	19"	1/16"	0.218	0.338		
CR127	6	23"	1/16"	0.218	0.338		
CR128	4	11"	3/32"	0.25	0.338	0.232	0.213
CR129	4	15"	3/32"	0.25	0.338		
CR130	4	19"	3/32"	0.25	0.338		
CR131	4	23"	3/32"	0.25	0.338		
CR132	3	11"	3/32"	0.277	0.38	0.26	0.238
CR133	3	15"	3/32"	0.277	0.38		
CR134	3	19"	3/32"	0.277	0.38		
CR135	3	23"	3/32"	0.277	0.38		
CR136	2	11"	3/32"	0.302	0.415	0.268	0.292
CR137	2	15"	3/32"	0.302	0.415		
CR138	2	19"	3/32"	0.302	0.415		
CR139	2	23"	3/32"	0.302	0.415		
CR140	1	11"	1/8"	0.36	0.474	0.299	0.332
CR141	1	15"	1/8"	0.36	0.474		
CR142	1	19"	1/8"	0.36	0.474		
CR143	1	23"	1/8"	0.36	0.474		
CR144	1/O	14"	1/8"	0.406	0.515	0.336	0.373
CR145	1/O	21"	1/8"	0.406	0.515		
CR146	1/O	28"	1/8"	0.406	0.515		
CR147	1/O	35"	1/8"	0.406	0.515		
CR148	2/O	14"	3/16"	0.44	0.58	0.376	0.419
CR149	2/O	21"	3/16"	0.44	0.58		
CR150	2/O	28"	3/16"	0.44	0.58		
CR151	2/O	35"	3/16"	0.44	0.58		
CR152	3/O	14"	3/16"	0.5	0.65	0.423	0.47
CR153	3/O	21"	3/16"	0.5	0.65		
CR154	3/O	28"	3/16"	0.5	0.65		
CR155	3/O	35"	3/16"	0.5	0.65		
CR156	4/O	14"	3/16"	0.5625	0.71	0.475	0.528
CR157	4/O	21"	3/16"	0.5625	0.71		
CR158	4/O	28"	3/16"	0.5625	0.71		
CR159	4/O	35"	3/16"	0.5625	0.71		
CR160	250	14"	1/4"	0.629	0.81	0.52	0.575
CR161	250	21"	1/4"	0.629	0.81		
CR162	250	28"	1/4"	0.629	0.81		



1325 Carden Farm Dr. Clinton, TN 37716 (865)670-3713

Crimp ID, OD, Specs for Alum & Copper

Crimp Part #	Conductor Size	Lanyard Length	Lanyard Wire Rope Diameter	Crimp IDin	Crimp OD in	Minimum Conductor Size (dia in)	Maximum Conductor Size (dia in)
CR163	250	35"	1/4"	0.629	0.81		
CR164	300	14"	1/4"	0.656	0.85	0.57	0.631
CR165	300	21"	1/4"	0.656	0.85		
CR166	300	28"	1/4"	0.656	0.85		
CR167	300	35"	1/4"	0.656	0.85		
CR168	350	14"	1/4"	0.718	0.93	0.616	0.681
CR169	350	21"	1/4"	0.718	0.93		
CR170	350	28"	1/4"	0.715	0.93		
CR171	350	35"	1/4"	0.718	0.93		
CR-172	400	14"	1/4"	0.75	0.966	0.659	0.737
CR173	400	21"	1/4"	0.75	0.966		
CR-174	400	28"	1/4"	0.75	0.966		
CR-175	400	35"	1/4"	0.75	0.966		
CR-176	500	14"	1/4"	0.846	1.11	0.736	0.814
CR-177	500	21"	1/4"	0.846	1.11		
CR178	500	28"	1/4"	0.846	1.11		
CR179	500	35"	1/4"	0.846	1.11		
CR180	600	14"	1/4"	0.905	1.2	0.813	0.893
CR181	600	21"	1/4"	0.905	1.2		
CR182	600	28"	1/4"	0.905	1.2		
CR183	600	35"	1/4"	0.905	1.2		
CR180	700AL	14"	1/4"	0.905	1.2	0.877AL	
CR181	700AL	21"	1/4"	0.905	1.2		
CR182	700AL	28"	1/4"	0.905	1.2		
CR183	700AL	35"	1/4"	0.905	1.2		
CR184	750	14"	1/4"	1.03	0.13	0.908	1.001
CR185	750	21"	1/4"	1.03	0.13		
CR186	750	28"	1/4"	1.03	0.13		
CR187	750	35"	1/4"	1.03	0.13		
CR184	900AL	14"	1/4"	1.03	0.13	0.999AL	
CR185	900AL	21"	1/4"	1.03	0.13		
CR186	900AL	28"	1/4"	1.03	0.13		
CR187	900AL	35"	1/4"	1.03	0.13		
CR188	1000	14"	1/4"	1.2	1.52	1.06	1.153
CR189	1000	21"	1/4"	1.2	1.52		
CR-190	1000	28"	1/4"	1.2	1.52		
CR191	1000	35"	1/4"	1.2	1.52		